

# GINTEC G20M

## KLÚČOVÉ VLASTNOSTI

- ◆ OEM Doska UM980
- ◆ 1408 kanálov
- ◆ Dizajn z horčíkovej zliatiny, hmotnosť 580g
- ◆ Príjem všetkých satelitných systémov
- ◆ RTK technológia
- ◆ IMU technológia kompatibilná s SurPad
- ◆ Rýchlonabíjacia technológia
- ◆ Kapacita batérie 9600mAh
- ◆ Inteligentné ovládanie cez webové rozhranie

Viac na  
[www.gintec.sk](http://www.gintec.sk)



Kompenzácia náklonu

GINTEC



GINTEC

# SPECIFICATIONS

## POSITIONING

Board Model	UM980
Channels	1408
GPS	L1 C/A, L2P(Y), L2C, L5
GLONASS	L1,L2
BEIDOU	B1I,B2I,B3I,B1C,B2a
GALILEO	E1, E5a, E5b
QZSS	L1, L2C,L5
Cold Start	<20s
Initialization Time	<5s
Initialization Reliability	>99.9%

## ACCURACY

Single Accuracy	H: 1.50m V: 2.50m
DGPS Accuracy	H: 0.40m V: 0.80m
RTK Accuracy	H:0.8cm 1ppm V:1.5cm 1ppm
Time Accuracy	20ns
Update Frequency	5HZ

## POWER

Battery	Built-in Battery,9600mAH 3.7V
Duratio	≥17h
Input	5V/2A DC

## PHYSICAL

Material	Magnesium alloy main body, ABS/PC top cover
Dimension	100mm *100mm*61.5
Weight	580g

## SYSTEM

Operation System	Linux
Memory	32GB Internal Storage
Bluetooth	V2.1+EDR/V4.0 Dual Mode
WIFI	802.11 a/b/g/n/ac
4G Network	LTE FDD:B1/B3/B5/B8 LTE TDD:B38/B39/B40/B41 TD-SCDMA:B34/B39 CDMA:BC0 WCDMA:B1/B8 GSM:900/1800 MHZ
Tilt Survey	IMU Tilt Survey Compatible with SurPad

## OPERATION

Button	Power Button
Indicator	Satellites,Datalink Bluetooth,Power

## ENVIRONMENT

Work Temperature	-20 °C~+60 °C
Stock Temperature	-40 °C~+80 °C
Waterproof/Dustproof	IP65 Standard
Shoch and Vibration	Withstand 1.5m pole drop onto the cement ground
Humidity	Humidity 100%



## Data Collector H6

Android 8.1  
5" HD screen  
6GB RAM/64GB ROM  
Full Keyboard  
IP67



QMARK s.r.o.  
Strojnícka 8, 821 05 Bratislava



[www.gintec.sk](http://www.gintec.sk)



[info@gintec.sk](mailto:info@gintec.sk)



GINTEC.SLOVAKIA



Mobile/Whatsapp  
+ 421 918 193 228